



Specifications

Processor	Intel Core 2 Duo 2.8GHz processor
Memory	2GB DDR2 RAM, 128MB flash (DOM)
HDD Capacity	8 x 3.5" or 2.5" SATA I/II HDD NOTE: <ol style="list-style-type: none"> 1. The system is shipped without HDD. 2. For the HDD compatibility list, please visit here
HDD Tray	8 x hot-swappable and lockable tray
LAN Port	2 x Gigabit RJ-45 Ethernet port
LED Indicators	Status, LAN, USB, HDD 1, HDD 2, HDD 3, HDD 4, HDD 5, HDD6, HDD7, HDD8
USB	5 x USB 2.0 (front:1; back:4) Front: for USB storage device (One touch auto video backup) Back: for UPS device
Buttons	Power, one touch auto video backup, reset
LCD Panel	LCD display with backlight Enter button, Select button for configuration
Alarm Buzzer	System warning
Form Factor	Tower
Dimensions	298(H) x 200(W) x 270(D) mm 11.73(H) x 7.87(W) x 10.63(D) inch
Color Box Shipping Weight	9.8Kg (21.61 lb)
Operation Environment	Temperature 0~40°C/ 32~104°F Humidity 0~95% R.H.
Power Supply	ATX 350W, input: 100-240 Vac~, 47-63Hz, 6A-2.8A
Power Consumption	81W Write/Read
Secure Design	K-Lock security slot for theft prevention
VGA	Reserved
Fan	2 x 12cm smart cooling fan
Certification	CE, FCC, VCCI, BSMI
Video	
Display Mode	1/ 4/ 6/ 8/ 9/ 10/ 12/ 16/ 20/ 25/ 36/ 42-channel display, Picture-in-Picture, sequential mode, multi-display mode
Number of Channels Supported (Recording)	Up to 40
Compression Format	H.264/ MxPEG/ MPEG-4/ M-JPEG (vary by camera models)
Video Setting	Resolution, Quality, Frame Rate
E-map	Upload E-map (JPEG)