

Description: 20 AWG RG59/U COAX CABLE
Compliance: UL13, CATV

Construction:

Conductor 20 AWG Copper Covered Steel

Insulation

Type Foamed Polyethylene
Color White
Thickness 0.055" nom.
Diameter 0.142" nom"

Shield

Tape Aluminum
Strands 0.0063" nom. Aluminum Wire
% Coverage 100% AL Tape - 40% AL Wire

Jacket

Type PVC
Color Black, White
Thickness 0.033" nom.
Diameter 0.244" nom.
Legend (Ink Print) **HONEYWELL P/N 5006 RG 59/U 20 AWG BROADBAND PREMIUM 3038058 (ETL)
TYPE CATV OR CL2 75C SUN. RES. W/O# XXXXXX-XXX XXXX FT (RoHS)
CATV/SATELLITE A B C D E F 1 2 3 4 5 6 7 8 9**

Properties

Voltage Rating 300 Volts
Temperature Rating -20 to 75 °C
Capacitance 17.3 pf/ft nom.
Impedance 75 Ohms nom.
Velocity of Propagation 78%
Resistance 21.7 Ohms/M' at 20°C
Attenuation (db/100') -0.65 at 1 MHz, -5.0 at 400 MHz, -8.15 at 1000 MHz
Flame Rating UL Vertical Tray